

GC50WPD

“When you see this boat, you realize three things. One, the design is unique. It is one of a kind. Two, the boat is striking and beautiful. And three, you realize that you’re staring at a boat that is capable of revolutionizing both the dive boat industry and how we transport divers to dive sites.”

- Joe Glacinto, *Sea Lion*



SPECIFICATIONS

Length	47' 5"
Beam	16'
Displacement	18,000 lbs.
Passengers	30
Propulsion	250 hp outboards
Cruise Speed	22 knots
Full Speed	28 knots

FEATURES

CONSTRUCTION DETAILS

Fir strip planked hull bottoms glassed inside with unidirectional E glass and stringer frame plywood topsides, exterior of hull glassed with triaxial glass Stringer/frame/plywood/fiberglassed cabin structure, beams, bridgedeck, extended roof and partitions. All materials marine grade, laminated, coated and glassed with WEST SYSTEM epoxy resin. Miscellaneous teak trim on bulkheads, roof and bar.

LAYOUT

Captain's seat, central aluminum framed bench seating with C-Cushions; side wall seating with dive tank storage; storage compartment, head with sink and toilet. Aft deck seat storage lockers. Rubber padded protected floor. 10' Custom dive platform with handrails and below water T ladders. Fixed plexiglass windshield. Roll up vinyl side windows.

FINISH

- Exterior Awlgrip Polyurethane paint over epoxy primer – commercial yacht finish.

PAINT & GRAPHICS

- Matterhorn White topsides and Aristo Blue window stripe, Black bottom paint.

TANKAGE

- 168 gallons fuel, 33 gallons water

ENGINE

- 2 –200 HP BETOUL Yamaha counter rotating outboards. Dual binnacle mount, tachometers, engine alarms, powertilt/trim. Teleflex hydraulic steering.

PLUMBING, PUMPS & FITTINGS

- All emergency piping is rigid PVC. Water supply hosing is rigid PVC and reinforced vinyl hose.
- 1 Henderson MKV emergency bilge pump.
- 1 Par Pressure pump with spigot and hose.
- 1 Raritan PHII hand toilet with Marelon thruhull and seacock.

ELECTRONICS

- Cassette Stereo with 2 speakers
- Standard Horizon Eclipse VHF
- 3" Danforth high speed compass
- Marinetics 12 Volt electrical panel with voltmeter
- Battery selector switch
- 90 amp. Starting batteries
- Port and starboard bowlight, sternlight and anchor/steaming light
- Interior fluorescent light fixture (head)
- Dome lights
- 12v outlet
- windshield wiper

SAFETY EQUIPEMENT

- 2 ABC 10 lb. fire extinguishers

GROUND TACKLE

- 22S Danforth, 15' 5/16" chain and 150' of 5/8" rode
- 20 lb. D2000 Danforth, 15' 5/16" chain and 150' of 5/8" rode
- 4 50 1/2" dock lines
- 4 Scanmarin fenders F4
- Full length rigid vinyl rubrail

DECK GEAR

- 4 12" SS cleats
- 2 10" SS cleats
- 6 24" SS handrails
- 2 Tempress small utility hatches
- 2 Lewmar Size 50 Ocean Hatches (hull access)
- Lewmar Size 50 Trimline Hatch (Captain's ventilion)

USCG Certification

Considered US built. Can be USCG certified for 30 passengers in a shuttle/ferry arrangement